FILED VIA EFS

ON 12/18/08

### IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re application of: George Zguris et al. Patent No. 7,160,824 Issued: January 9, 2007

Application No. 10/630,546

Filed: July 29, 2003 Confirmation No. 7494

For: GLASS COMPOSITIONS

Examiner: Gwendolyn A. Blackwell Rudasil

Art Unit: 1775

Attorney Reference No. 3533-66350-01

FILED VIA ELECTRONIC FILING SYSTEM COMMISSIONER FOR PATENTS

## REQUEST FOR CERTIFICATE OF CORRECTION

The following printing errors were noted in comparing the printed patent with the papers in the attorneys' files:

#### In the Specification:

Column 1, lines 26 and 27, "working temperatures (about 1427°C.)." should read --working temperatures (temperature ranges between glass viscosity 100 and 10000 poise) of about 2600°F (about 1427°C).--.

Column 8, line 44, "(F2)" should read --(F2)--.

Column 8, line 51, "SiO2, A1203" should read --SiO2, A12O3--.

Column 8, line 57, "TiO2" should read --TiO2--.

Column 8, line 29, "TiO2" should read --TiO2--.

Column 14, line 11, "at plate" should read --at the plate--.

Since not all of the errors are attributable to the Patent Office, the fee of \$100.00 pursuant to 37 C.F.R. 1.20(a) is being submitted electronically herewith. The preceding corrections

remedy mistakes of a typographical nature and/or minor character. The Certificate of Correction is enclosed to make formal notice of the errors in the referenced patent.

Respectfully submitted,

KLARQUIST SPARKMAN, LLP

One World Trade Center, Suite 1600 121 S.W. Salmon Street

Portland, Oregon 97204 Telephone: (503) 595-5300

Facsimile: (503) 595-5301

у \_

Lisa M. Caldwell Registration No. 41,653 Staple Here Only

# UNITED STATES PATENT AND TRADEMARK OFFICE CERTIFICATE OF CORRECTION

PATENT NO. : 7,160,824

DATED : January 9, 2007

INVENTOR(S) : George Zguris et al.

It is certified that an error appears or errors appear in the above-identified patent and that said Letters Patent is hereby corrected as shown below:

## In the Specification:

Column 1, lines 26 and 27, "working temperatures (about 1427°C.)." should read — working temperatures (temperature ranges between glass viscosity 100 and 10000 poise) of about 2600°F (about 1427°C).—.

Column 8, line 44, "(F2)" should read --(F2)--.

Column 8, line 51, "SiO2, A1203" should read -- SiO2, A12O3--.

Column 8, line 57, "TiO2" should read -- TiO2 --.

Column 8, line 29, "TiO2" should read -- TiO2 ---.

Column 14, line 11, "at plate" should read --at the plate--.